



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Andrew Gersey

Dated

11 February 2004

Patents Form 1/77

Patents Act 1977
(Rule 6)

The
Patent
Office

1/77

Request for grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales NP10 8QQ

| | | | |
|---|--|---|------------------------------------|
| 1. Your reference | A10505GB-DJL/scf 01MAR02 E700226 1 D02011 P01/7700 0.00-0204886.6 | | |
| 2. Patent application number (The Patent Office will fill in this part) | 0204886.6 | | |
| 3. Full name, address and post code of the or of each applicant (underline all surnames) | Honeywell Normalair-Garrett (Holdings) Limited Westland Works Yeovil Somerset BA20 2YD United Kingdom Patents ADP number (if you know it) If the applicant is a corporate body, give the country/state of its incorporation | | |
| | 7937915001 UNITED KINGDOM | | |
| 4. Title of the invention | Breathing Gas Supply System | | |
| 5. Name of your agent (if you have one) | Forrester Ketley & Co. | | |
| "Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode) | Chamberlain House Paradise Place Birmingham, B3 3HP. Patents ADP number (if you know it) 133005 | | |
| 6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number | Country | Priority application number (if you know it) | Date of filing (day/month/year) |
| 7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application | Number of earlier application | Date of filing (day/month/year) | |
| 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if: a) any applicant named in part 1 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d)) | Yes | | |

Patents Form 1/77

- Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form -

Description 9

Claim(s) 3

Abstract 1 *DM*Drawing(s) 1 *only*

10. If you are also filing any of the following, state how many against each item.

Priority documents NONE

Translation of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11. I/We request the grant of a patent based on the basis of this application

Signature

Forrester Ketley & Co.

Forrester Ketley & Co.

Date

1 March, 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

D J Lucking

0121 236 0484

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- if you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

0030294 01-Mar-02 04:45

PATENTS ACT 1977

A10505GB/DJL

Title: Breathing Gas Supply System

Description of Invention

This invention relates to a breathing gas system for supplying breathable gas in an aircraft to aircrew and/or passengers.

It is known to provide a supply of compressed oxygen or oxygen enriched gas in an aircraft for emergency use, for example in the event of a cabin depressurisation at high altitude. Such supply is usually contained in gas bottles which are heavy and bulky. Accordingly it is usual to provide only a limited emergency gas supply sufficient for breathing while the aircraft altitude is reduced to an altitude where the ambient air may be breathed.

During normal flight, a substantial proportion of the cabin air which is breathed is recirculated, and this results in a deterioration in air quality particularly noticeable on long haul flights. However to refresh the cabin air by decreasing the proportion of air which is recirculated can incur a significant cost penalty in terms of fuel consumption, as ambient air would need to be pressurised up to cabin pressure and possibly heated, before it can be introduced into the cabin for breathing, although compressed air from an engine compressor may be used but this usually needs cooling before it can be used.

In any event, even if a greater proportion of the cabin air was replenished, the maximum oxygen concentration in the cabin air cannot be greater than in the ambient air, but the partial pressure of the oxygen will be less than ideal because the cabin is not pressurised to sea level but to about 5 - 8000 ft above sea level. Hence the concentration of oxygen in normally breathed air in an aircraft flying at typical cruising altitudes of 35-40,000 ft say, is always, with conventional systems, less than desirable.

It is known to use a molecular sieve bed type of apparatus to adsorb non-oxygen gas from compressed air which may be bled from the aircraft engine or engines, and thus supply a product gas for breathing at pressure, which is highly enriched in oxygen. However such apparatus are themselves heavy and bulky and have not been widely adopted for civilian aircraft use where fuel economy is a prime consideration, but are more usually used in military aircraft to provide a supply of breathing for aircrew when the aircraft is operating at altitude and/or on high G-maneuvres in non-pressurised cabins.

According to a first aspect of the invention we provide a breathing gas supply system for supplying breathable gas in an aircraft including an oxygen enriching apparatus which is operable in at least two modes to provide product gas with varying oxygen concentrations, a first feed line to feed more highly enriched product gas to one or more breathing gas outlets, and a second feed line to feed less highly enriched product gas for breathing, and a control means to control the oxygen enrichment apparatus to provide highly enriched product gas to the breathing gas outlet or outlets in the first mode of operation or less highly enriched product gas for breathing, and to control a diverter valve which directs the product gas to the respective feed line.

Preferably in the first mode of operations the more highly enriched product gas is fed to a plurality of gas outlets e.g. for emergency use, and in the second mode of operation the less highly enriched product gas is fed to an aircraft cabin for breathing during normal high altitude flight.

Thus in a system in accordance with the invention, the function of providing for a supply of breathable gas in the event of an emergency decompression may be achieved in a common apparatus which provides for the function of providing oxygen enriched gas to the aircraft cabin for normal breathing. The problem of economically providing for fresh cabin air is ameliorated, by supplying oxygen enriched air to the cabin, without having

separate normal breathing and emergency breathing systems, but a common system is provided for both.

Preferably the oxygen enriching apparatus includes a plurality of molecular sieve beds which are operable cyclically to adsorb non-oxygen gas during a charging phase to produce product gas for breathing, and de-adsorb non-oxygen gas to atmosphere during a venting phase to clean the bed of non-oxygen gas.

Desirably, the product gas produced in the second mode of operation has about a 40-60% oxygen concentration and more particularly about 50%, whilst the product gas produced in the first mode of operation has about a 70-90% oxygen concentration, and more typically about 80%. However preferably the product gas produced in the second mode of operation is diluted, for example with recirculated cabin air e.g. from an air conditioning unit, prior to introduction into the cabin for normal breathing so that the oxygen concentration of the air breathed normally in the cabin is not significantly greater than that of ambient air, so as not to present a fire risk for example. Typically the concentration of air breathed in the cabin is arranged to be about 22-23%.

It is known to control the concentration of oxygen in the product gas to achieve a desired oxygen concentration e.g. for altitude, by varying the charge to vent ratio during an operating period, or to maintain the ratio fixed and change the operating period. To perform such control it is necessary to provide an oxygen sensor to sense the concentration of oxygen in the product gas and a sophisticated control means.

Alternatively it is known to operate the molecular sieve beds of the oxygen enriching apparatus to produce a maximum concentration of oxygen, and then to dilute the highly enriched product gas to achieve a desired oxygen concentration for breathing.

Generally a molecular sieve bed operates most efficiently to produce a given flow of product gas with a maximum oxygen concentration with a charge to vent ratio of 1:1 but operating an oxygen enriching apparatus which includes a plurality of molecular sieve beds most efficiently, whilst being able to accommodate varying operating conditions i.e. varying product gas demand and varying oxygen concentration, is not straightforward, because different size and hence weight molecular sieve beds operate most efficiently to produce different concentrations of oxygen for a given flow of product gas. For example if it is desired to produce a given flow of product gas with say, 50% oxygen, there is an optimum size of molecular sieve bed, which will be different to that producing a different given flow of oxygen gas with say, 80% oxygen concentration.

In accordance with the present invention preferably the oxygen enriching apparatus includes N molecular sieve beds and in the first mode of operation X beds are operated to produce the highly enriched product gas at a flow rate of Y , where $X < N$, and in the second mode of operation all N beds are operated to produce the less highly enriched product gas at a flow rate Z , where Z is greater than Y .

It will be appreciated that a greater volume of product gas will need to be produced for normal cabin breathing than for emergency use and thus normal cabin breathing represents the greatest demand for product gas volume.

By providing the minimum capacity apparatus necessary to meet the maximum envisaged demand, the size and weight of the oxygen enriching apparatus may be optimised.

Preferably the control means is capable of switching the oxygen enriching apparatus between operating modes and of optimising use of the oxygen enriching apparatus when operating at less than maximum demand. For example the control means may be programmed to select X of the N molecular

sieve beds to operate when less than the maximum demand is required to be fulfilled, and an operating cycle to operate those selected beds most efficiently.

During maximum demand, in the second mode of operation, when all N beds are operated, preferably each bed is operated in sequence with a charge to vent ratio of about 1:N so that each bed is charging i.e. adsorbing non-oxygen gas and producing product gas, for about an equivalent time in any operating period, and venting for the maximum time possible.

In the first mode of operation when X of the N beds is operating, each of the X beds may be operated in sequence with a charge to vent ratio of about 1:X so that each bed is charging i.e. adsorbing non-oxygen gas and producing product gas, for about an equivalent time in any operating period, and venting for the maximum time possible, while the non-selected N-X beds are not operated.

However in conditions of lesser demand, the X beds may alternatively be operated optimally to match the production of breathable gas to the demand. For example the X beds may be operated with a variable or fixed charge to vent ratio, in accordance with prior art practices.

The invention will now be described with reference to the accompanying drawing which is a schematic view of a breathing gas supply system in accordance with the invention.

Referring to the drawing, a breathing gas supply system 10 for supplying breathable gas to aircrew and/passengers in an aircraft cabin 11, includes an oxygen enriching apparatus 12 which in this example includes a plurality of molecular sieve beds, i.e. N beds, each of which is operable cyclically to adsorb non-oxygen gas from a compressed air supply 14, during a charging phase to produce product gas for breathing, and de-adsorb non-oxygen gas and ventilate to atmosphere during a venting phase to clean the bed of non-oxygen gas.

The compressed air supply 14 is derived in this example from an engine compressor, and air flow to and vented air flow from the beds of the oxygen

enriching apparatus 10 is controlled by a control valve 15 arrangement which is illustrated in a simplified form only.

In use, the oxygen enriching apparatus 12 provides product gas either to the aircraft cabin 11 for normal breathing, or to breathing masks 17 in the cabin for emergency use, for example in the case of a sudden emergency cabin 11 decompression, depending on the position of a diverter valve 20.

When the diverter valve 20 is in a first position, product gas is fed into a first feed line 22 to which are connected, the breathing masks 17, for example via "T" valves 18. When the diverter valve 20 is in a second position, product gas is fed into a second feed line 24, and hence to the cabin 11 for normal breathing via a mixing apparatus 25 to which recirculated cabin air from a cabin air conditioning unit 26 may be provided, to dilute the product gas prior to its introduction into the cabin 11.

The diverter valve 20 is controlled by a control means 30 which also controls the charge/vent valve arrangement 15, and the operation of the molecular sieve beds of the oxygen enriching apparatus 12 too.

The volume of product gas required to be introduced into the cabin 11 for normal breathing will be substantially greater than the volume of product gas required for emergency breathing. This is because some cabin air is exhausted from the cabin 11 in order to control the temperature within the cabin 11, which air has to be replaced. However the concentration of oxygen in the product gas will be required to be much lower for normal breathing than in an emergency situation when the cabin pressurisation is lost.

The greatest demand for product gas is for normal breathing because of the high product gas flow required. The molecular sieve beds of the oxygen enriching apparatus 12 may optimally be operated in an aircraft flying at typical cruising altitudes, to produce for a maximum gas flow, an oxygen concentration of about 50% in the product gas.

Hence: in designing an oxygen enriching apparatus 12, the maximum capacity of product gas production is to be catered for is for a given product gas flow with such an oxygen concentration. However this is too great a concentration for normal breathing in the pressurised cabin, and accordingly the product gas is diluted in the mixing apparatus by mixing the 50% concentration oxygen in the second feed line 24 with recirculated cabin air to achieve a desired oxygen concentration in the product gas/recirculated air mixture fed to the cabin 11. For a cabin pressurised at say, 5000 ft, desirably the oxygen concentration in the product gas/recirculated air is in the order of 22-23%.

Where: there is maximum demand for product gas, the N molecular sieve beds of the oxygen enriching apparatus 12 are preferably operated sequentially with a charge to vent ratio of 1:N. Thus each bed will be adsorbing non-oxygen gas from the compressed air supply 14 a generally equal amount so that the beds will age equally, and each bed will be vented for the maximum period possible in any operating period.

In the first mode of operation of the oxygen enriching apparatus 12 when highly concentrated oxygen enriched product gas is required for breathing in an emergency decompression situation, a smaller volume of product gas will be required and so the amount of compressed air fed to the oxygen enriching apparatus 12 can be reduced. At the same time, even though a more highly concentrated product gas is required, because the gas flow is reduced the demand on the oxygen enriching apparatus 12 is reduced. Thus all N molecular sieve beds need not continue to be operated. Rather X beds of the N may be selected by the control means 30 for operation.

The X beds of the oxygen enriching apparatus 12 may be operated sequentially with a charge to vent ratio of 1:X. Thus each of the X beds will be adsorbing non-oxygen gas from the compressed air supply 14 a generally equal amount and each bed will be vented for the maximum period possible in any

operating period. If desired to ensure that all the N beds will age equally, the X beds selected to be operated in the first mode of operation may be sequenced.

However the selected X beds may be alternatively controlled for optimal operation. For example a pair or pairs of the molecular sieve beds of the oxygen enriching apparatus 12 may be operated with a variable charge to vent ratio, or alternative fixed charge to vent ratios or otherwise to achieve a desired flow of product gas with a desired oxygen concentration.

Desirably the oxygen concentration in the product gas in the first mode of operation which is diverted by the diverter valve 20 to the first feed line 22, is about 80% which is adequate to sustain life at typical civilian aircraft cruising altitudes of around 40,000 ft. in a depressurised cabin 11.

Because the emergency supply is provided by an oxygen enrichment apparatus 12, there is no need, as with conventional systems which utilise a limited supply of compressed oxygen stored for emergency use, for the aircraft height rapidly to be reduced to a lower altitude, say 10,000 ft at which ambient air may comfortably be breathed, but if desired the aircraft cruising height may be maintained or more probably, the aircraft altitude reduced in a much slower and comfortable manner than is necessary with conventional systems in an emergency decompression situation.

In the second mode of operation, when demand on the oxygen enrichment apparatus 12 is at a maximum, preferably all N beds are operated, in sequence, with a charge to vent ratio of about 1:N so that each bed is charging i.e. adsorbing non-oxygen gas and producing product gas, for about an equivalent time in any operating period, and venting for the maximum time possible.

In the figure it can be seen that there is an oxygen monitor 32 downstream of the oxygen enriching apparatus 12 but upstream of the diverter valve 20, to monitor the correct operation of the oxygen enriching apparatus 12. The input to the control means 30 from the oxygen monitor 32 may be used by

the control means to determine an operating regime for the selected X beds of the oxygen enriching apparatus 12. Also, there is an oxygen sensor 33 in the cabin 11 to provide another input to the control means 30, to check and/or take remedial action in the event that the oxygen concentration in the cabin falls below or exceeds acceptable levels. There may also be provided an altitude sensor 34 which may provide another input to the control means 30 to enable the concentration of oxygen in the cabin air to be closely controlled depending on altitude, if desired.

Various modifications may be made without departing from the scope of the invention. For example in the first mode of operation, instead of supplying product gas for an emergency decompression situation, product gas from the oxygen enrichment apparatus 12 may be used for other purposes such as for a supply of highly concentrated oxygen gas for therapeutic purposes, where for example the aircraft is carrying sick or injured passengers, or for an oxygen supply for aircrew only.

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. A breathing gas supply system for supplying breathable gas in an aircraft including an oxygen enriching apparatus which is operable in at least two modes to provide product gas with varying oxygen concentrations, a first feed line to feed more highly enriched product gas to one or more breathing gas outlets, and a second feed line to feed less highly enriched product gas for breathing, and a control means to control the oxygen enrichment apparatus to provide highly enriched product gas to the breathing gas outlet or outlets in the first mode of operation or less highly enriched product gas for breathing, and to control a diverter valve which directs the product gas to the respective feed line.
2. A system according to claim 1 wherein in the first mode of operations the more highly enriched product gas is fed to a plurality of gas outlets, and in the second mode of operation the less highly enriched product gas is fed to an aircraft cabin for breathing during normal high altitude flight.
3. A system according to claim 1 or claim 2 wherein the oxygen enriching apparatus includes a plurality of molecular sieve beds which are operable cyclically to adsorb non-oxygen gas during a charging phase to produce product gas for breathing, and de-adsorb non-oxygen gas to atmosphere during a venting phase to clean the bed of non-oxygen gas.
4. A system according to claim 1 or claim 2 or claim 3 wherein the product gas produced in the second mode of operation has about a 40-60% oxygen concentration, and more particularly about 50%, whilst the product gas produced in the first mode of operation has about a 70-90% oxygen concentration, and more typically about 80%.

produced in the first mode of operation has about a 70-90% oxygen concentration, and more typically about 80%.

5. A system according to any one of the preceding claims wherein the product gas produced in the second mode of operation is diluted for use.

6. A system according to claim 5 wherein the product gas produced in the second mode of operation is diluted for use with recirculated cabin air prior to introduction into the cabin for normal breathing so that the oxygen concentration of the air breathed normally in the cabin is not significantly greater than that of ambient air.

7. A system according to claim 6 wherein the oxygen concentration of the air breathed normally in the cabin is about 22-23%.

8. A system according to any one of the preceding claims wherein the oxygen enriching apparatus includes N molecular sieve beds and in the first mode of operation X beds are operated to produce the highly enriched product gas at a flow rate of Y, where $X < N$, and in the second mode of operation all N beds are operated to produce the less highly enriched product gas at a flow rate Z, where Z is greater than Y.

9. A system according to claim 8 wherein the control means is capable of switching the oxygen enriching apparatus between operating modes and of optimising use of the oxygen enriching apparatus when operating at less than maximum demand.

10. A system according to claim 9 wherein the control means is programmed to select X of the N molecular sieve beds to operate when less than the

12

maximum demand is required to be fulfilled, and an operating cycle to operate those selected beds.

11. A system according to claim 8 or claim 9 wherein in the second mode of operation, all N beds are operated, and each bed is operated in sequence with a charge to vent ratio of about 1:N.

12. A system according to any one of claims 8 to 11 wherein in the first mode of operation when X of the N beds is operating, each of the X beds is operated in sequence with a charge to vent ratio of about 1:X.

13. A breathing gas system substantially as hereinbefore described with reference to and as shown in the accompanying drawings.

14. Any novel feature or novel combination of features described herein and/or as shown in the accompanying drawings.

ABSTRACT**Breathing Gas Supply System**

A breathing gas supply system (10) for supplying breathable gas in an aircraft includes an oxygen enriching apparatus (12) which is operable in at least two modes to provide product gas with varying oxygen concentrations, a first feed line (22) to feed more highly enriched product gas to one or more breathing gas outlets (17), and a second feed line (24) to feed less highly enriched product gas e.g. to an aircraft cabin (11) for breathing during normal high altitude flight, and a control means (30) to control the oxygen enrichment apparatus (12) to provide highly enriched product gas to the breathing gas outlet or outlets (17) in the first mode of operation or less highly enriched product gas e.g. to the cabin (11) for normal breathing, and to control a diverter valve (20) which directs the product gas to the respective feed line (22, 24).

